

Coaxial Cable RG6 95BEM

CENTER CONDUCTOR : 21 AWG COPPER-CLAD STEEL

NOMINAL DIAMETER : 0.040" (1.02 mm)

DIELECTRIC : GAS EXPANDED POLYETHYLENE

NOMINAL DIAMETER OVER DIELECTRIC : 0.180" (4.57 mm)

SHIELD : 1ST SHIELD : LAMINATED ALUMINUM TAPE BONDED TO THE DIELECTRIC
NOMINAL DIAMETER OVER TAPE : 0.187" (4.75 mm)

2ND SHIELD : 34 AWG ALUMINUM BRAID WIRE 75% COVERAGE

JACKET : PE

NOMINAL DIAMETER OVER JACKET : 0.272" (6.7 mm)

NOMINAL JACKET THICKNESS : 0.030" (0.76 mm)



ELECTRICAL PROPERTIES :

IMPEDANCE : 75.0 +/- 3.0 Ohms

VELOCITY OF PROPAGATION : 85.0% NOMINAL

ATTENUATION : @ 68°F (20°C)

Kanal	Frekuensi (MHz)	RG695-BE/M
S2	112	6
E10	210	8
S21	303	10
S34	407	12
U25	503	14
U30	543	15
U38	607	17
U50	703	18
U55	743	18
E69	855	19

Jumlah Serabut Aluminium 96 (6*16)

Impedansi (Ω) 75

Resistansi DC (Ω) 31